

Trade Name MasimoSol 2050

Product Code MAS 2012

Product Category Mineral Spirits / White

CAS Registry

EINCES Number

Description MasimoSol 2050 is a wide cut mixture of paraffins, cycloparaffins and aromatics that boils in between 200 and 250°C. As a consequence of its increased boiling range level, MasimoSol 2050 can be considered as a high flash, slow evaporating type of hydrocarbon solvent.

Characteristic Properties		Test Method	Units	Min	Max	Typical
Appearance		Visual	n/a	Report		Clear & Bright
Colour		ASTM D156	Saybolt	25		+30
Density@20°C		ASTM D4052	Kg/l	0,800		0,808
Distillation:	IBP	ASTM D1078	·c	198	205	203
	50%V		·c	Report		220
	DP		·c	240	260	250
Flash Point		ASTM D93	·c	80	90	85
Aromatic		ASTM D1319	%Vol	15	22	18
Sulphur		ASTM D5453	%m	0,05		0,03
Doctor Test		ASTM D4952	-ve/+ve	-ve		Negative
Aniline Point		ASTM D611	·c	Report		63
Viscosity@25°C		ASTM D445	cST	1,8	2,3	2,1

Trademark

MasimoSol is a Masimo Chemicals South Africa (Pty) Ltd trademark.

Warranty / Disclaimer

All products purchased or supplied by Masimo Chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Masimo Chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Masimo Chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based on the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.