



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Name	MasimoSol D90
CAS -No.	64742-47-8
Synonyms	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Supplier	Masimo Chemicals South Africa (Pty) Ltd G9 Arbour Grove Office Park 10 Oppenheimer Road Amazimtoti, Durban, 4126
Emergency telephone South Africa	+27 (0) 82 430 9754 +27 (0) 83 638 0165

Recommended use of the chemical and restrictions on use

Recommended use	Industrial Solvent
Restrictions on use	This product must not be used in applications other than the above without first seeking the advice of the supplier.

2. HAZARDS IDENTIFICATION

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard : Category 1



Label Elements
Hazards pictograms :



Signal word	:	Danger
Hazard Statement	:	PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: H304 May be fatal if swallowed and enters airways. ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.
Supplemental Hazard Statement	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	Prevention: P243 Take action to prevent static discharge. Response: P301+ P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor. P331 Do NOT induce vomiting. Storage: P405 Store locked up. Disposal: P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.
Other Hazards	:	May form flammable/explosive vapour-air mixture. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Chemical nature : A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Naphtha (Petroleum), Hydrotreated Light	64742-47-8	Xn; R65-R66	Asp. Tox. 1; H304 EUH066	100

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

General Advice : Not expected to be a health hazard when used under normal conditions.

If Inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice

In case of Skin Contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention

In case of Eye Contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention

If Swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility,



Most Important Symptoms and Effects, Both Acute and Delay	:	fever greater than 101°F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	:	Potential for chemical pneumonitis. Call a doctor or poison control centre for guidance.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	:	Do not use water in a jet.
Specific hazards during fire fighting	:	Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.
Specific extinguishing methods	:	Standard procedure for chemical fires. Keep adjacent containers cool by spraying with water.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).



6. ACCIDENTIAL RELEASE MEASURE

- Personal Precautions, Protective Equipment and Emergency Procedures : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
- Local authorities should be advised if significant spillages cannot be contained.
- Avoid contact with skin, eyes and clothing.
- Isolate hazard area and deny entry to unnecessary or unprotected personnel.
- Do not breathe fumes, vapour.
- Do not operate electrical equipment.
- Environmental Precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Monitor area with combustible gas indicator.
- Methods and Materials for Containment and Cleaning Up : For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- Ventilate contaminated area thoroughly. If contamination of site occurs, remediation may require specialist advice.
- Additional advice : For guidance on selection of personal protective equipment, see Chapter 8 of this Safety Data Sheet.
- For guidance on disposal of spilled material, see Chapter 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

- General Precautions : Avoid breathing of or direct contact with material. Only use in well-ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment, see Chapter 8 of this Safety Data Sheet.
- Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed.
- Advice on Safe Handling : Avoid inhaling vapour and/or mists.
- Avoid contact with skin, eyes and clothing.
- Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
- Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
- Bulk storage tanks should be diked (bunded). When using do not eat or drink.
- The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Avoidance of contact : Strong oxidising agents.
- Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Refer to guidance under Handling section.
- Storage**
- Conditions for safe storage : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.



Other Data : Storage Temperature: Ambient.
 Bulk storage tanks should be diked (bunded).
 Locate tanks away from heat and other sources of ignition.
 Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
 Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products, which are not harmful or toxic to man or to the environment.
 Electrostatic charges will be generated during pumping.
 Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
 The vapours in the headspace of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packing Material : Suitable material: For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.
 Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific Use(s) : Not Applicable
 See additional references that provide safe handling practices for liquids that are determined to be static accumulators:
 American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or
 National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
 IEC/TS 60079-32-1: Electrostatic hazards, guidance.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters /Permissible concentration	Basis
RCP Dearom.	Not Assigned	TWA	1.200 mg/m3	OEL based on



Mineral Spirits 175 - 220				European Hydrocarbon Solvents Producers (CEFIC-HSPA) methodology.
Further information: Recommended Limit				

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>
Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>
L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>.

Engineering Measures : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

- Use sealed systems as far as possible.
- Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
- Local exhaust ventilation is recommended.
- Firewater monitors and deluge systems are recommended.
- Eye washes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is



greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Personal Protective Equipment : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Protective measures

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers.

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].

Hand Protection : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves.

Remarks

For continuous contact we recommend gloves with

breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers.

Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

- | | | |
|---------------------------------|---|---|
| Eye protection | : | If material is handled such that it could be splashed into eyes, protective eyewear is recommended. |
| Skin and body protection | : | <p>Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure.</p> <p>If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.</p> <p>Wear antistatic and flame retardant clothing, if a local risk assessment deems it so.</p> |
| Thermal Hazard | : | Not applicable. |
| Hygiene Measures | : | <p>Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.</p> <p>Do not ingest. If swallowed then seek immediate medical assistance.</p> |
| Environmental Exposure Controls | | |
| General Advice | : | <p>Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.</p> <p>Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.</p> <p>Information on accidental release measures are to be found in section 6.</p> |

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Colourless
Odour	Paraffinic
Odour Threshold	Data no available
pH	Not applicable
Melting point/Freezing Point	< -30 °C/-22 °F
Boiling point and boiling range	Typical 225 - 275 °C/437-527 °F
Flash Point	Typical 95 °C/203 °F Method: ASTM D-93 / PMCC
Evaporation rate	0,01 Method: ASTM D 3539, nB u Ac = 1 3,900 Method: DIN 53170, di-ethyl ether=1
Upper Explosion Limit	5,5 %(V)
Lower Explosion Limit	0,6 %(V)
Vapour Pressure	0,01 kPa (20 °C / 68 °F)
Relative vapour density	Data not available
Relative density	Data not available
Density	Typical 788 kg/m ³ (15 °C / 59 °F) Method: ASTM D4052
Solubility (ies) Water Solubility	Insoluble
Partition coefficient: n-octanol/water	log Pow: 6,5-8,7
Auto-ignition temperature	231°C/448°F Method: ASTM E-659 220°C/428°F Method: DIN 51794
Decomposition temperature	Data not available

Viscosity	
Viscosity, dynamic	Data not available
Viscosity, kinematic	Typical 1,97 mm ² /s (25 °C / 77 °F)
Explosive properties	Not classified
Oxidising properties	Data not available
Surface tension	Data not available
Conductivity	Low conductivity: < 100 pS/m. The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.
Molecular weight	190 g/mol

10. STABILITY AND REACTIVITY

- Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
- Chemical Stability : No hazardous reaction is expected when handled and stored according to provisions Stable under normal conditions of use.
- Possibility of Hazardous Reactions : Reacts with strong oxidising agents.
- Conditions to Avoid : Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.
- Incompatible Materials : Strong oxidising agents
- Hazardous Decomposition Products : Hazardous decomposition products are not expected to form during normal storage.
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on product testing, and/or similar products, and/or components.

Information on likely Route of Exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact and accidental ingestion.

Acute toxicity

Product:

Acute Oral Toxicity : LD50 Rat: >5000 mg/kg
Remarks: Low toxicity:

Acute Inhalation Toxicity : Rat: Exposure time: 4h
Remarks: Low toxicity:
LC50 greater than near-saturated vapour concentration.

Acute Dermal Toxicity : LD50 Rabbit: > 5000 mg/kg
Remarks: Low toxicity:

Skin Corrosion/Irritation

Product:

Remarks : Causes mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

Serious Eye Damage / Eye Irritation

Product:

Remarks : Not irritating to eye.

Respiratory or Skin Sensitisation

Product:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product:

Remarks : Not mutagenic.

Carcinogenicity

Product:

Remarks : Tumours produced in animals are not considered relevant to humans. Not expected to be carcinogenic. Based on available



data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Distillates (Petroleum), Hydrotreated Light	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Distillates (Petroleum), Hydrotreated Light	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

Reproductive Toxicity

Product:

Remarks : Not a development toxicant. Based on available data, the classification criteria are not met. Does not impair fertility.

STOT – Single Exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

STOT – Repeated Exposure

Product:

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans.

Aspiration Toxicity

Product:

Remarks : Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further Information

Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for assessment : Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.



Ecotoxicity

Product:

Toxicity to fish (Acute toxicity)

Remarks

: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met

Toxicity to crustacean (Acute toxicity)

Remarks:

: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met

Toxicity to algae / aquatic plants (Acute toxicity)

Remarks:

: LC/EC/IC50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity)

Remarks:

: Data not available

Toxicity to crustacean (Chronic toxicity)

Remarks:

: Data not available

Toxicity to microorganisms (Acute toxicity)

Remarks

: Data not available

Persistence and degradability

Product:

Biodegradability

Remarks:

: Readily biodegradable, Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulative potential

Product:

Bioaccumulation

Remarks:

: Has the potential to bioaccumulate.

Partition coefficient: n-

: Log Pow: 6,5 - 8,7



octanol/water

Mobility in soil

Product:

Mobility

Remarks : Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

Other adverse effects : No data available.

Product:

Additional ecological information : Physical properties indicate that hydrocarbon gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in watercourses.
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Disposal should be in accordance with applicable regional, national and local laws and regulations.
Local regulations may be more stringent than regional or national requirements and must be complied with.
- Contaminated packing : Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.
Send to drum recover or metal reclaimer.
Comply with any local recovery or waste disposal regulations.

14. TRANSPORT INFORMATION

International Regulations



IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

Additional Information : This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other international regulations

The components of this product are reported in the following inventories:

DSL	:	Listed
IECSC	:	Listed
KECI	:	Listed
PICCS	:	Listed
EINECS/ELINCS/EC	:	Listed
TSCA	:	Listed

16. OTHER INFORMATION

Full text of R-Phrases

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Full text of H-Statements

EUH066 Repeated exposure may cause skin dryness or cracking.



H304 May be fatal if swallowed and enters airways.

Full text of other abbreviations

Asp. Tox. Aspiration hazard

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

SDS Regulations :

Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Masimo Chemicals, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.