



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

As of the revision date above, this safety data sheet meets the regulations in Southern African Development Community (SADC) member states.

Product Name	MasimoSol GTL G70
Registration number:	01-0000020119-75
Synonyms	Distillates (Fischer-Tropsch) C8-26 – branched and linear
CAS-No	848301-67-7
EC-No	481-740-5

Relevant identified uses of the substances or mixture and uses advised against

Use of the Substance/ Mixture	Solvent. Please refer to Ch16 for the registered uses under REACH.
Uses advised against	This product must not be used in applications other than the above without first seeking the advice of the supplier.
Supplier	Masimo Chemicals South Africa (Pty) Ltd G9 Arbour Grove Office Park 10 Oppenheimer Road Amanzimtoti, Durban, 4126
Emergency telephone South Africa	+27 (0) 82 430 9754 +27 (0) 83 638 0165

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1 : H304: May be fatal if swallowed and enters airways.

Label Elements

Labelling (REGULATION (EC) No 1272/2008)



Hazard Pictograms:

Signal word	:	Danger
Hazard statements	:	<p>PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria.</p> <p>HEALTH HAZARDS: H304 May be fatal if swallowed and enters airways.</p> <p>ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.</p>
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<p>Prevention: P243 Take action to prevent static discharge.</p> <p>Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor. P331 Do NOT induce vomiting.</p> <p>Storage: P405 Store locked up.</p> <p>Disposal: P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.</p>
Other hazards	:	<p>The substance does not fulfil all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.</p> <p>May ignite on surfaces at temperatures above auto-ignition temperature.</p> <p>Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range.</p> <p>This material is a static accumulator.</p> <p>Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.</p> <p>If sufficient charge is allowed to accumulate, electrostatic</p>



discharge and ignition of flammable air-vapour mixtures can occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Hazardous components

Chemical name	CAS-No. EC-No	Concentration [%]
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear	848301-67-7 481-740-5	< = 100

4. FIRST-AID MEASURES

Description of first aid measures

- General advice : DO NOT DELAY.
Keep victim calm. Obtain medical treatment immediately.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

Most important symptoms and effects,



both acute and delayed

Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
The onset of respiratory symptoms may be delayed for several hours after exposure.
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.
Call a Poison Control Centre for guidance.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing Media : Do not use water in a jet.

Special hazards arising from the substance or mixture

Specific hazards during firefighting : Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Will float and can be reignited on surface water.

Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Standard procedure for chemical fires.



Further information : Keep adjacent containers cool by spraying with water.

6. ACCIDENTIAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained.

For non-emergency personnel:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

For emergency responders:
Avoid contact with skin, eyes and clothing.
Isolate hazard area and deny entry to unnecessary or unprotected personnel.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

Environmental Precautions

: Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

Methods and materials for containment and cleaning up

Methods for cleaning up : For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an



appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly.

If contamination of site occurs remediation may require specialist advice.

Reference to other sections : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Ensure that all local regulations regarding handling and storage facilities are followed.

Precautions for safe handling

Advice on safe handling : Avoid inhaling vapour and/or mists.

Avoid contact with skin, eyes and clothing.

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

Bulk storage tanks should be diked (bunded).

When using do not eat or drink.

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is



allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Refer to guidance under Handling section.

Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers :

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Other data :

Storage Temperature: Ambient.

Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or to the environment. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire.

Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.

Packaging material :

Suitable material: For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.

Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.

Container Advice

Do not cut, drill, grind, weld or perform similar operations on or near containers.

Specific end use(s)



Specific use(s) : Please refer to Ch16 and/or the annexes for the registered uses under REACH.
Please refer to Ch16 and/or the annexes for the registered uses under REACH.
Not applicable.
See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Occupational exposure limits : In the absence of a national exposure limit, the American Conference of Governmental Industrial Hygienists (ACGIH) recommends the following values for Diesel Fuel: TWA - 100 mg/m³ Critical effects based on Skin and Irritation.

Biological occupational exposure limits : No biological limit allocated.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006: : No DNEL value has been established.

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006: : Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

Monitoring Methods : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.
For some substances biological monitoring may also be appropriate.
Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.
Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
National Institute of Occupational Safety and Health (NIOSH),

USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>
Occupational Safety and Health Administration (OSHA), USA:
Sampling and Analytical Methods <http://www.osha.gov/>
Health and Safety Executive (HSE), UK: Methods for the
Determination of Hazardous Substances
<http://www.hse.gov.uk/>
Institut für Arbeitsschutz Deutschen Gesetzlichen
Unfallversicherung (IFA) , Germany
<http://www.dguv.de/inhalt/index.jsp>
L'Institut National de Recherche et de Sécurité, (INRS), France
<http://www.inrs.fr/accueil>

Exposure controls

Engineering measures

: Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Use sealed systems as far as possible.
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Firewater monitors and deluge systems are recommended.
Eye washes and showers for emergency use.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

: Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.
Practice good housekeeping.
Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.



- Personal protective equipment : Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.
The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.
- Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Approved to EU Standard EN166.
- Hand protection
- Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.
Application of a non-perfumed moisturizer is recommended.
- Skin and body protection : Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes.
Protective clothing approved to EU Standard EN14605.
Wear antistatic and flame retardant clothing, if a local risk



- assessment deems it so.
- Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. If air-filtering respirators are suitable for conditions of use: Select a filter suitable for organic gases and vapours meeting EN14387 [Filter type A, for use against certain organic gases and vapours with a boiling point > 65°C (149°F)].
- Hygiene measures : Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed then seek immediate medical assistance.
- Environmental exposure controls**
- General advice : Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to wastewater. Wastewater should be treated in a municipal or industrial wastewater treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid
------------	--------

Colour	Colourless
Odour	Paraffinic
Odour Threshold	Data not available
pH	Data not available
Pour point	- 21 °C
Boiling point/boiling range	> 150 °C
Flash point	> = 70 °C
Evaporation rate	Data not available
Flammability (solid, gas)	Not applicable
Upper explosion limit	6% (V)
Lower explosion limit	0,5 % (V)
Vapour pressure	< 0,001 kPa (25 °C)
Relative vapour density	Data not available
Relative density	Data not available
Density	ca. 0,78 g/cm ³ (20 °C)
Solubility(ies) Water solubility	Insoluble
Partition coefficient: n-octanol/water	log Pow: > 6,5
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity Viscosity, dynamic	Data not available
Viscosity, kinematic	< 7 mm ² /s (40 °C)
Explosive properties	Not classified
Oxidizing properties	Not applicable
Other information Surface tension	Data not available
Conductivity	Low conductivity: < 100 pS/m. The conductivity of this material makes it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity

	is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

10. STABILITY AND REACTIVITY

- Reactivity : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
- Chemical stability : No hazardous reaction is expected when handled and stored according to provisions, Stable under normal conditions of use.

Possibility of hazardous reactions

- Hazardous reactions : Reacts with strong oxidising agents.
- Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.

Incompatible materials

- Materials to avoid : Strong oxidising agents.

Hazardous decomposition products

- : Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

- Basis for assessment : Information given is based on product data, a knowledge of the components and the toxicology of similar products.
- Information on likely routes of exposure : Inhalation is the primary route of exposure although absorption may occur through skin contact or following accidental ingestion.

Acute toxicity

Product:



- Acute oral toxicity : LD50 Rat: > 5.000 mg/kg
Remarks: Low toxicity
- Acute inhalation toxicity : LC50: > 5 mg/l
Exposure time: 4 h
Remarks: Low toxicity by inhalation.
- Acute dermal toxicity : LD50 Rat: > 2000 mg/kg
Remarks: Low toxicity
- Skin corrosion/irritation Product : Remarks: Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not irritating to skin.
- Serious eye damage/eye irritation**
Product : Remarks: Not irritating to eye.
- Respiratory or skin sensitisation**
Product : Remarks: Not a sensitizer. Based on available data, the classification criteria are not met.
- Germ cell mutagenicity**
Product : Remarks: Not mutagenic.
- Carcinogenicity**
Product: : Remarks: Not a carcinogen. Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear	No carcinogenicity classification

- Reproductive toxicity Product : Remarks: Does not impair fertility. Not a developmental toxicant. Based on available data, the classification criteria are not met.
- STOT - single exposure Product : Remarks: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
- STOT - repeated exposure Product : Remarks: Based on available data, the classification criteria are not met.



Aspiration toxicity
Product : Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

12. ECOLOGICAL INFORMATION

Toxicity
Basis for assessment : Information given is based on product testing.

Product:

Toxicity to fish (Acute toxicity) : LC50: > 100 mg/l
Remarks: Practically non-toxic

Toxicity to crustacean (Acute toxicity) : EC50: > 100 mg/l
Remarks: Practically non-toxic

Toxicity to algae/aquatic plants (Acute toxicity) : EC50: > 100 mg/l
Remarks: Practically non-toxic

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 100 mg/l

Toxicity to crustacean (Chronic toxicity) : Remarks: NOEC/NOEL > 10 - < =100 mg/l

Toxicity to microorganisms (Acute toxicity) : IC50: > 100 mg/l
Remarks: Practically non-toxic

Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: > 6,5

Mobility in soil

Product:

Mobility : Remarks: Floats on water. Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day.



Large volumes may penetrate soil and could contaminate groundwater.

Results of PBT and vPvB assessment

Product:

Assessment

: The substance does not fulfil all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

Other adverse effects

Product:

Additional ecological information

: Films formed on water may affect oxygen transfer and damage organisms.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Product

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging

: Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

Send to drum recoverer or metal reclaimer.

Comply with any local recovery or waste disposal regulations.

14. TRANSPORT INFORMATION



UN number

ADN : 9003
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

Proper shipping name

ADN : SUBSTANCES WITH FLASHPOINT > 60°C BUT NOT MORE THAN 100 °C
(Distillates (Fischer-Tropsch), C8-26, branched and linear)
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

Transport hazard class

ADN : 9
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

Packing group

ADN
Packing group : Not Assigned
Labels : 9 (F)
CDNI Inland Water Waste Agreement : NST 8963 Solvent
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

Environmental hazards

ADN



Environmental hazards	:	No
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
Special precautions for user		
Remarks	:	Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	::	Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.
Additional Information	:	This material is not regulated under ADR, RID and does not meet criteria of class 3 for ADN regulations as per section 2.2.3.1.1 (Note 1) and subsection 32.2.5 of Part III of the Manual of Tests and Criteria. This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances (Seveso III).

Directive 2004/37/EC on the protection of workers from the



risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

The components of this product are reported in the following inventories:

DSL	:	Listed
ENCS	:	Listed
KECI	:	Listed
PICCS	:	Listed
EINECS/ELINCS/EC	:	Listed
TSCA	:	Listed
Chemical safety assessment	:	A Chemical Safety Assessment was performed for all substances of this product.

16. OTHER INFORMATION

Abbreviations and Acronyms:

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
DSL = Canada Domestic Substance List
EC = European Commission
EC50 = Effective Concentration fifty
ECETOC = European Centre on Ecotoxicology and Toxicology Of Chemicals
ECHA = European Chemicals Agency
EINECS = The European Inventory of Existing Commercial Chemical Substances
EL50 = Effective Loading fifty
ENCS = Japanese Existing and New Chemical Substances Inventory
EWC = European Waste Code
GHS = Globally Harmonised System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Inhibitory Concentration fifty
IL50 = Inhibitory Level fifty
IMDG = International Maritime Dangerous Goods
INV = Chinese Chemicals Inventory
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI = Korea Existing Chemicals Inventory
LC50 = Lethal Concentration fifty
LD50 = Lethal Dose fifty per cent.
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
LL50 = Lethal Loading fifty
MARPOL = International Convention for the Prevention of Pollution From Ships
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level
OE_HP V = Occupational Exposure - High Production Volume
PBT = Persistent, Bioaccumulative and Toxic
PICCS = Philippine Inventory of Chemicals and Chemical Substances
PNEC = Predicted No Effect Concentration
REACH = Registration Evaluation And Authorisation Of Chemicals



Further information

Other information

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

The eSDS(s) received to date have been reviewed for the registered components in this mixture. The advice provided in the body of this SDS covers all necessary Risk Management Measures.

For Industry guidance and tools on REACH please visit the CEFIC website at <http://cefic.org/Industry-support>.

The substance does not fulfil all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

This product is classified as H304 (May be fatal if swallowed and enters airways). The risk relates to potential for aspiration.

The risk arising from aspiration hazard is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Chapter 8 of the SDS. An exposure scenario is not presented.

This product is classified as R66 / EUH066 (Repeated exposure may cause skin dryness or cracking). The risk relates to the potential for repeated or prolonged dermal contact. The risk arising from contact is solely related to the physico-chemical properties of the substance. The risk can therefore be controlled by implementing risk management measures tailored to this specific hazard and included within Chapter 8 of the SDS. An exposure scenario is not presented.

Sources of key data used to compile the Safety Data Sheet:

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Masimo Chemicals, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Identified Uses according to the Use Descriptor System

Uses - Worker

Title:

Industrial



Manufacture of substance
Distribution of substance
Formulation & (re)packing of substances and mixtures
Use in Oil and Gas field drilling and production operations
Use in Cleaning Agents
Lubricants
Metal working fluids / rolling oils
Use as a fuel
Use as binders and release agents
Water treatment chemicals
Uses in Coatings
Functional Fluids
Road and construction applications
Use in laboratories
Rubber production and processing
Polymer processing
Mining chemicals
Use as an intermediate

Uses - Worker

Title

Professional
Use as a fuel
Use in Cleaning Agents
Use in agrochemicals
Lubricants
Metal working fluids / rolling oils
Use as binders and release agents
Water treatment chemicals
Uses in Coatings
Functional Fluids
Road and construction applications
Use in laboratories
Explosives manufacture & use
Polymer processing

Uses - Consumer

Title

Consumer
Use in Cleaning Agents
Use in Agrochemicals uses
Lubricants



Masimo Chemicals South Africa (Pty) Ltd

Safety Data Sheet

MasimoSol GTL G70

Use as a fuel
Uses in Coatings
Functional Fluids
Other Consumer Uses

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.