



**Product Name** MasimoSol GTL G85

**Product Category** Synthetic Paraffins

**CAS Registry Number** 848301-67-7

**EINECS Number** 481-740-05

**Description** MasimoSol GTL G85 is a high performance fluid derived from natural gas feedstock converted into synthetic paraffins with state of the art catalyst technology. Because of this combination of gaseous feedstock and intensive process control, undesirable impurities (i.e. aromatics, olefins, sulfur, etc...) are virtually non-detectable. This process technology delivers a unique mixture of inert C8-C26 synthetic paraffins which provide discerning users consistently with:

- clean burning characteristics
- low cloud/ freeze/ pour point
- low odor
- low toxicity
- low vapor pressure
- low viscosity
- ready biodegradability

MasimoSol GTL G85 is part of the MasimoSol range of products which can be provided in varying flash points and viscosities.

**Typical Properties**

Property	Unit	Method	Value
API Gravity	-	ASTM D4052	49.8
Specific Gravity @ 15.6°C/15.6°C [60°F/60°F]	-	ASTM D4052	0.780
Density @ 15.6°C [60°F]	kg/L	ASTM D4052	0.780
Density @ 15.6°C [60°F]	lb/gal	ASTM D4052	6.51
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	780
Coefficient of Cubic Expansion @ 20°C	10 <sup>-4</sup> /°C	Calculated	9
Refractive Index @ 20°C	-	ASTM D1218	1.436
Color	Saybolt	ASTM D156	+30
Copper Corrosion (1hr @ 100°C)	-	ASTM D130	1a

Distillation, Initial Boiling Point	°C	ASTM D86	198
Distillation, Final Boiling Point	°C	ASTM D86	343
Relative Evaporation Rate (nB u Ac = 1)	-	ASTM D3539	< 0.01
Relative Evaporation Rate (Ether=1)	-	DIN 53170	> 3900
Vapor Pressure @ 20°C	kPa	Calculated	0.02
Vapor Pressure @ 50°C	kPa	Calculated	< 0.01
Saturated Vapor Concentration @ 20°C	g/m <sup>3</sup>	Calculated	1.7
Volatile Organic Compound (VOC)	g/L	EU / EPA	780
Paraffins	% m/m	GC	98
Naphthenes	% m/m	GC	2
Aromatics	mg/kg	SMS 2728	< 500
Benzene	mg/kg	GC	< 5
Sulfur	mg/kg	ISO 20846	< 1
Flash Point	°C	ASTM D93	86
Flame Sustainability @ 75°C	-	ISO 9038	Pass
Lower Explosion Limit in Air	% v/v		0.5
Upper Explosion Limit in Air	% v/v		6.0
Auto Ignition Temperature	°C	ASTM E659	205
Electrical Conductivity @ 25°C	pS/m	IEC 60247	< 0.1
Electrical Constant @ 25°C	-	IEC 60247	2.05
Breakdown Voltage	kV/2.5mm	ASTM 1816	66
Ash content	% m/m	ISO 6245	< 0.001
Smoke Point	Mm	ASTM D1322	> 50
Aniline Point	°C	ASTM D611	95
Kauri-Butanol Value	-	ASTM D1133	24
Cloud Point	°C	ASTM D2500	-18



Cold Filter Plugging Point	°C	IP 309	-18
Pour Point	°C	ASTM D97	-27
Hildebrand Solubility Parameter	(cal/cm <sup>3</sup> ) <sup>1/2</sup>	-	7.5
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Surface Tension @ 20°C	mN/m	-	28
Viscosity @ 25°C	mm <sup>2</sup> /s	ASTM D445	4.0
Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D445	2.9
Molecular Weight	g/mol	Calculated	213

### Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM): [www.astm.org](http://www.astm.org)  
International Electrotechnical Commission (IEC): [www.iec.ch](http://www.iec.ch)  
International Organization for Standardization (ISO): [www.iso.org](http://www.iso.org)  
Deutsches Institut für Normung (DIN): [www.din.de](http://www.din.de)

### Quality

MasimoSol GTL G85 does not contain detectable quantities of heavy metals and chlorinated compounds.

### Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet on [www.masimochem.com/](http://www.masimochem.com/).

### Storage and Handling

Provided proper storage and handling precautions are taken we would expect MasimoSol GTL G85 to be technically stable for at least 12 months. All detailed advice on Storage and Handling please refer to the Safety Data Sheet on [www.masimochem.com/](http://www.masimochem.com/).

### Trademark

MasimoSol is a Masimo Chemicals South Africa (Pty) Ltd trademark.

### Warranty/Disclaimer

All products purchased or supplied by Masimo Chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by



Masimo Chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Masimo Chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based on the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.