



Product Category	Special Boiling Point Solvents
CAS Registry Number	64742-49-0
EINECS Number	265-151-9
Product Description	SBP 100/140 is a C7-C9 hydrocarbon solvent. Being made from hydrogenated feedstock, its aromatics and olefins content is very low.

Typical Properties

Properties	Unit	Method	Value
Water	% m/m	ASTM D1364	< 0.005
Density @15 °C	kg/L	ASTM D4052	0.732
Coefficient of Cubic Expansion @ 20 °C	10 ⁻⁴ /°C	Calculated	12
Refractive Index 20 °C	-	ASTM D1218	1.406
Colour	Saybolt	ASTM D156	+30
Bromine Index	mg Br/100g	ASTM D1492	< 5
Copper Corrosion (1hr @ 100 °C)	-	ASTM D130	1
Doctor Test	-	ASTM D4952	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	1
Distillation, Initial Boiling Point	°C	ASTM D1078	106
Distillation, Dry Point	°C	ASTM D1078	136
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	1.9
Relative Evaporation Rate (Ether=1)	-	DIN 53170	6
Antoine Constant A #	kPa, °C	-	7.51210
Antoine Constant B #	kPa, °C	-	2541.50
Antoine Constant C #	kPa, °C	-	349.980
Antoine Constants: Temperature range	°C	-	+40 to +105
Vapor Pressure @ 0 °C	kPa	Calculated	1.8
Vapor Pressure @ 20 °C	kPa	Calculated	4.4
Saturated Vapor Concentration @ 20 °C	g/m ³	Calculated	198



Paraffins	% m/m	GC	60
Naphthenes	% m/m	GC	40
Aromatics	mg/kg	SMS 2728	< 5
Benzene	mg/kg	GC	< 3
n-Hexane	% m/m	GC	< 0.1
Sulfur	mg/kg	ISO 20846	< 0.5
Flash Point, (Abel)	°C	IP170	1
Lower Explosion Limit in Air	% v/v		0.9
Upper Explosion Limit in Air	% v/v		6.8
Auto Ignition Temperature	°C	ASTM E659	310
Electrical Conductivity @ 20 °C	pS/m	ASTM D4308	< 1
Dielectric Constant @ 20 °C	-	-	2.0
Aniline Point	°C	ASTM D611	63
Kauri-Butanol Value	-	ASTM D1133	33
Pour Point	°C	ASTM D97	< -50
Viscosity @ 25 °C	mm ² /s	ASTM D445	0.72
Surface Tension @ 20 °C	mN/m	Du Nouy ring	22
Thermal Conductivity @ 20 °C	W/m/ °C		0.13
Hildebrand Solubility Parameter	(cal/cm ³) ^{1/2}	-	7.5
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization at, T _{boil}	kJ/kg	-	300
Heat of Combustion (Net) @t 25 °C	kJ/kg	-	45500
Specific Heat @ 20 °C	kJ/kg/°C	-	2.1
Molecular Weight	g/mol	Calculated	110

(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T(°C) can be calculated by means of the Antoine equation: $\log P = A - B/(T+C)$.

Test Methods



Masimo Chemicals South Africa (Pty) Ltd

Technical Data Sheet

MasimoSol SBP 100/140

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society of Testing and Materials (ASTM)
International Organization for Standardization (ISO)
Deutsches Institut für Normung (DIN)

www.astm.org

www.iso.org

www.din.de

MaximoSol methods are issued by Masimo Chemicals. Requests for copies of SMS can be made through Masimo Chemicals South Africa (Pty) Ltd.

N.B: For routine quality control local test methods may be applied. Such methods have been validated against those mentioned in this datasheet.

Quality

MasimoSol SBP 100/140 does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet on <https://masimochem.com/>.

Storage Handling

Provided proper storage and handling precautions are taken we would expect MasimoSol SBP 100/140 to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet on <https://masimochem.com/>.

Warranty/Disclaimer

All products purchased or supplied by Masimo Chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Masimo Chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Masimo Chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based on the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.